

M60D ENHANCED

7.62x51 mm NATO
Part Number: 29051

Specifications

Caliber	7.62x51 mm NATO
Max Effective Range	1100 Meters (1200 yds)
Max Range	3725 Meters (4075 yds)
Muzzle Velocity	853 m/s (2800 fps)
Rate of Fire (cyclic)	500-600 Rounds per minute

Weight	11.03 kg (24.32 lbs)
Length	1111 mm (43.75 In)
Width	146 mm (5.75 In)



Weapon

The M60D Enhanced is a mounted version of the standard M60E6. It can be mounted on boats, vehicles or as a pintle-mounted door gun in helicopters. The M60D Enhanced features a redesigned machined aluminum feed cover with integrated M1913 Picatinny rail for the mounting of optics and a forward M1913 Picatinny rail for other sensors, giving the weapon 24 hour capability. The M60D Enhanced is a gas operated, disintegrating link, belt fed, air-cooled machine gun. It fires from an open bolt and features a quick-change Chromium Cobaltlined lined barrel. The M60D Enhanced is fitted with spade grips for flexible use and an aircraft ring sight for rapid target acquisition. A canvas bag can be affixed to the gun to capture ejected casings and links, preventing them from being sucked into the rotor blades or into an engine intake. The M60D Enhanced is used on the UH-1B Huey (using the M23, XM29, M59, and the Sagami mounts), the CH-47 Chinook (using the M24 and M41 mounts) in both door and ramp locations, the ACH-47A "Guns-A-Go-Go" variant of the Chinook (using the XM32 and XM33 mounts), and on the UH-60 Black Hawk (using the M144 mount). An "egress kit" or "infantry modification kit" is available to provide downed aircrew personnel with increased fire power but the weapon is configured with a bipod and sling mount for ground use in the existing configuration.

Key Features

- Reliable and user-friendly.
- M1913 Picatinny rail topcover for mounting optics and forward M1913 rail for mounting laser aiming devices and other sensors giving the weapon 24 hour capability.
- Improved feedcam assembly eliminates charging jams and improves operator safety by allowing a belt loaded but not charged feature. The 30% improved belt pull provides increased reliability
- Chromium Cobaltlined sustained fire barrels for extended barrel life.
- All major components are directly interchangeable with other M60D configurations.
- Fail-safe reversible gas piston with simplified gas system.
- Offset barrel handle provides a clear sight picture and eliminates the need for a heat mitten for barrel changes.
- Lightweight one-hand operated receiver mounted bipod eliminates the weight of the bipod on the spare barrel.
- Hard chrome and induction hardening of oprod tube facilitates easier cleaning and increases the service life of the receiver.
- Upgrade kits available for older M60D machine guns.

U.S. ORDNANCE
300 West Sydney Drive, Ste. 101
McCarran, NV 89437
United State of America

TEL: 775.343.1320
FAX: 775.343.1331
EMAIL: sales@usord.com
WEB: usord.com
CAGE CODE: 1NZNO

ISO 9001:2015
QUALITY MANAGEMENT SYSTEM
CERTIFIED BY DNV
100% USA Made

Available via Direct Commercial Purchase (DCS) or via FMS on long term contract W52H0909D0135.

Warranty: Your US Ordnance firearm is warranted against defects in materials and/or workmanship for two year from date of original new gun or conversion kit purchase.