



•• DEFENSE SYSTEMS ••

U.S. ORDNANCE

••• MANUFACTURING •••

USORD.COM

M60D ENHANCED

7.62 mm NATO
Part Number: 29051

Specifications

Caliber	7.62 mm NATO
Max Effective Range	1100 Meters (1200 yds)
Max Range	3725 Meters (4075 yds)
Muzzle Velocity	853 m/s (2800 fps)
Rate of Fire (cyclic)	500-600 Rounds per minute
Weight	11.03 kg (24.32 lbs)
Length	1111 mm (43.75 In)
Width	146 mm (5.75 In)



Weapon

The M60D Enhanced is a mounted version of the standard M60E4/Mk43. It can be mounted on boats and vehicles, or as a pintle-mounted door gun in helicopters. The M60D Enhanced features a redesigned machined aluminum feed cover with integrated M1913 Picatinny rail for mounting optics and a forward M1913 Picatinny rail for other sensors, giving the weapon 24-hour capability.

The M60D Enhanced is a gas-operated, disintegrating-link, belt-fed, air-cooled machine gun. It fires from an open bolt and features a quick-change Stellite®-lined barrel. It is fitted with spade grips for flexible use and an aircraft ring sight for rapid target acquisition. A canvas bag can be affixed to the gun to capture ejected casings and links, preventing them from being sucked into the rotor blades or into an engine intake. The M60D Enhanced is used on the UH-1B Huey (using the M23, XM29, M59 and Sagami mounts), the CH-47 Chinook (using the M24 and M41 mounts) in both door and ramp locations, the ACH-47A "Guns-A-Go-Go" variant of the Chinook (using the XM32 and XM33 mounts) and on the UH-60 Black Hawk (using the M144 mount). An "egress kit," or "infantry modification kit," is available to provide downed aircrew personnel with increased fire power. However, the weapon's usual configuration is with a bipod and sling mount for ground use.

Key Features

- Reliable and user friendly
- M1913 Picatinny rail top-cover for mounting optics and forward M1913 Picatinny rail for mounting laser-aiming devices and other sensors, giving the weapon 24-hour capability.
- Improved feedcam assembly eliminates charging jams and improves operator safety by allowing a belt loaded, but not charged, feature; the 30% improved belt pull increases reliability
- Stellite®-lined sustained fire barrels
- All major components directly interchange with other M60D configurations
- Fail-safe reversible gas piston with simplified gas system
- Offset barrel handle provides a clear sight picture and eliminates needing a heat mitten for barrel changes
- Lightweight, one hand-operated, receiver-mounted bipod eliminates bipod weight on the spare barrel
- Hard chrome and induction hardening of the op rod tube facilitates easier cleaning and increases the receiver service life
- Upgrade kits are available for older M60D machine guns

U.S. ORDNANCE, INC.
300 West Sydney Drive, Ste. 101
McCarran, NV 89434
United State of America

TEL: 775.343.1320
FAX: 775.343.1331
EMAIL: sales@usord.com
WEB: usord.com
CAGE CODE: 1NZN0

ISO 9001:2008
QUALITY MANAGEMENT SYSTEM
CERTIFIED BY DNV

100% USA Made

Available via Direct Commercial Purchase (DCS) or via FMS on long term contract W52H0909D0135.

Warranty: Your US Ordnance firearm is warranted against defects in materials and/or workmanship for two year from date of original new gun or conversion kit purchase.

© 2010 U.S. Ordnance, Inc. All Rights Reserved. Stellite® is a registered trademark of the Cabot Corporation.